

Package: pushbar (via r-universe)

October 11, 2026

Title Create Sliders for 'Shiny'

Version 0.1.0

Date 2019-07-13

Description Create sliders from left, right, top and bottom which may include any html or 'Shiny' input or output.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Imports shiny, jsonlite

RoxygenNote 7.1.1

URL <https://github.com/JohnCoene/pushbar>

BugReports <https://github.com/JohnCoene/pushbar/issues>

Config/pak/sysreqs cmake make libuv1-dev zlib1g-dev

Repository <https://johncoene.r-universe.dev>

Date/Publication 2022-11-09 23:11:21 UTC

RemoteUrl <https://github.com/johncoene/pushbar>

RemoteRef HEAD

RemoteSha a94d2b777901491e8ba304dc118c7c958c6da352

Contents

pushbar	2
pushbar-buttons	3
pushbar_style	4
Index	5

pushbar

Setup Pushbar

Description

Set up pushbar.

Creates element containing pushbar content.

Usage

```
pushbar_deps()
```

```
setup_pushbar(blur = FALSE, overlay = TRUE, esc_close = TRUE)
```

```
pushbar(  
  ...,  
  id = from,  
  from = c("left", "right", "top", "bottom"),  
  class = NULL,  
  style = pushbar_style()  
)
```

Arguments

blur	Whether to blur the background when pushbar is opened.
overlay	Whether to darken the background when pushbar is opened.
esc_close	Whether to enable pressing 'ESC' key to close the pushbar
...	Any other valid tags .
id	Id of pushbar.
from	Wherefrom the pushbar should open.
class	Additional class to pass to div.
style	Valid css defaults to pushbar_style .

Details

Creates a div.

Note

You are advised to add padding inside your pushbar i.e.: `style="padding:20px;"`

Examples

```
library(shiny)

ui <- fluidPage(
  pushbar_deps(),
  actionButton("open", "Open pushbar"),
  pushbar(
    h4("HELLO")
  )
)

server <- function(input, output, session){

  setup_pushbar()

  observeEvent(input$open, {
    pushbar_open()
  })
}

if(interactive()) shinyApp(ui, server)
```

pushbar-buttons*Pushbar Buttons*

Description

Open and close pushbar programatically.

Usage

```
pushbar_open(id = c("left", "right", "top", "bottom"))

pushbar_close()
```

Arguments

id Id of pushbar to open.

pushbar_style	<i>Style</i>
---------------	--------------

Description

Default pushbar CSS, used in [pushbar](#).

Usage

`pushbar_style()`

Index

pushbar, [2](#), [4](#)
pushbar-buttons, [3](#)
pushbar_close (pushbar-buttons), [3](#)
pushbar_deps (pushbar), [2](#)
pushbar_open (pushbar-buttons), [3](#)
pushbar_style, [2](#), [4](#)

setup_pushbar (pushbar), [2](#)

tags, [2](#)