

Package: pushbar (via r-universe)

October 29, 2024

Title Create Sliders for 'Shiny'

Version 0.1.0

Date 2019-07-13

Description Create sliders from left, right, top and bottom which may include any html or 'Shiny' input or output.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Imports shiny, jsonlite

RoxygenNote 7.1.1

URL <https://github.com/JohnCoene/pushbar>

BugReports <https://github.com/JohnCoene/pushbar/issues>

Repository <https://johncoene.r-universe.dev>

RemoteUrl <https://github.com/johncoene/pushbar>

RemoteRef HEAD

RemoteSha a94d2b777901491e8ba304dc118c7c958c6da352

Contents

pushbar	2
pushbar-buttons	3
pushbar_style	4

Index	5
--------------	----------

pushbar

Setup Pushbar

Description

Set up pushbar.

Creates element containing pushbar content.

Usage

```
pushbar_deps()
```

```
setup_pushbar(blur = FALSE, overlay = TRUE, esc_close = TRUE)
```

```
pushbar(  
  ...,  
  id = from,  
  from = c("left", "right", "top", "bottom"),  
  class = NULL,  
  style = pushbar_style()  
)
```

Arguments

<code>blur</code>	Whether to blur the background when pushbar is opened.
<code>overlay</code>	Whether to darken the background when pushbar is opened.
<code>esc_close</code>	Whether to enable pressing 'ESC' key to close the pushbar
<code>...</code>	Any other valid tags .
<code>id</code>	Id of pushbar.
<code>from</code>	Wherefrom the pushbar should open.
<code>class</code>	Additional class to pass to div.
<code>style</code>	Valid css defaults to pushbar_style .

Details

Creates a div.

Note

You are advised to add padding inside your pushbar i.e.: `style="padding: 20px;"`

Examples

```
library(shiny)

ui <- fluidPage(
  pushbar_deps(),
  actionButton("open", "Open pushbar"),
  pushbar(
    h4("HELLO")
  )
)

server <- function(input, output, session){

  setup_pushbar()

  observeEvent(input$open, {
    pushbar_open()
  })
}

if(interactive()) shinyApp(ui, server)
```

pushbar-buttons

Pushbar Buttons

Description

Open and close pushbar programatically.

Usage

```
pushbar_open(id = c("left", "right", "top", "bottom"))

pushbar_close()
```

Arguments

id Id of pushbar to open.

<code>pushbar_style</code>	<i>Style</i>
----------------------------	--------------

Description

Default pushbar CSS, used in [pushbar](#).

Usage

```
pushbar_style()
```

Index

pushbar, [2](#), [4](#)
pushbar-buttons, [3](#)
pushbar_close (pushbar-buttons), [3](#)
pushbar_deps (pushbar), [2](#)
pushbar_open (pushbar-buttons), [3](#)
pushbar_style, [2](#), [4](#)

setup_pushbar (pushbar), [2](#)

tags, [2](#)